

Anchor Setting Table Type ASV 80-GNT

Product description

- Setting Equipment for installation of fischer undercut anchors with anchor-nut

Advantages

- Easy to operate
- Compact size, table top support removable
- No supply lines necessary
- Optical-acoustical torque control

Technical details

- Solid framework with water-resistant wooden board
- Compact dimensions, table top support can be removed
- Accu operated anchor setting tool for a torque controlled installation
- Quick charger and second battery included
- Deposit cup for FZP anchors
- Checking gauges for hole size and anchor torque verification
- Tools for maintenance and adjustments

Operation steps

1. Put on facade panel
2. Place FZP-Anchor into setting adapter
3. Position setting tool above undercut hole and insert FZP-Anchor into the hole
4. Press the anchor downwards with little force and start setting tool until machine is stopped by pre-set torque
5. Place more FZP Anchors
6. Remove facade panel



Technical details

Dimensions	ca. 102 x 92 x 120 cm (W x D x H)
Total weight (without crate packing)	ca. 66 kg
Weight for table top support only	ca. 17,5 kg
Weight for tool box with accessories only	ca. 7,5 kg
Table dimensions	ca. 100 x 90 cm (W x D)
Table height	ca. 84 cm
Maximum / minimum swivel range (radius)	ca. 995 / 350 mm
Suitable for panel size (without use of additional tables)	ca. max. 110 x 90 cm
Performance	Time for setting procedure for one anchor: ca. 10-15sec. (without handling of panel)
Costs / Configuration	for hires and purchase costs refer to separate list

ACT Service

fischerwerke GmbH & Co. KG

Werk Altheim · Hindenburgstr. 81 · D-72160 Horb
 Phone +49 (0)74 43 12-45 53 · Fax +49 (0)74 43 12-49 07
 act@fischer.de · www.fischer.de