

Battery Operated Setting Tool Type SGB

Product Description

Electro-mechanic Setting Tool to install fischer FZP Flush Installation Undercut Anchors

Advantages

- Cableless
- High pulling strength
- Designed for use of façade panels in a thickness 2 cm up.
- Constant speed and automatic switching to drill-off at the end of setting process
- Separate triggering of the pulling step
- Quick mandrel exchange up.

Technical Details (range of delivery)

- Delivery includes metal carrying case, battery and quick battery charger
- On demand a second battery is included
- Nosepieces and threaded mandrels for fischer FZP Flush Installation Undercut Anchors (M6 and M8) with bolt projection length >10mm

Operation Steps

1. Insert FZP Anchor through the nosepieces and turn it slightly into the mandrel inside
2. Put FZP Anchor into the undercut hole, hold the tool vertical to panel surface and lead it downwards with a little load in direction anchor-drill-hole axis.
3. Pressing the trigger- Threaded bolt of FZP Anchor is threaded on
4. Pressing the trigger a second time – by leading the tool downwards with a little load the FZP- Anchor will be expanded into the undercut. The tool turns into automatic drill-off mode at the end of setting process.



Technical Details

Dimensions (Metal carrying case)	345 x 275 x 90 mm (B x T X H)
Total weight (including second battery)	5.5 kg
Setting Tool	
Weight (setting tool)	2.1 kg (incl. battery)
Operating voltage	12 Volt DC
Pulling strength	13,000 N
Battery	
Nominal Voltage	14.4 V
Nominal Capacity	1.3 Ah
Cell composition	Li-Ion battery. No memory effect.
Weight	0.35 kg
Quick battery charger	
Input voltage	230V/50 Hz (optional 115V/60Hz)
Charging time	approx. 1-1.5 hour
Weight	0.6 kg
Costs / Configuration	on request

ACT Service

fischerwerke GmbH & Co. KG

Weinhalde 14-18 · D-72178 Waldachtal

Phone +49 (0)74 43 12-45 53 · Fax +49 (0)74 43 12-49 07

act@fischer.de · www.fischer.de